



US005467107A

**United States Patent** [19]

DiSanto et al.

[11] **Patent Number:** **5,467,107**[45] **Date of Patent:** **Nov. 14, 1995**

[54] **ELECTROPHORETIC DISPLAY PANEL  
WITH SELECTIVE CHARACTER  
ADDRESSABILITY**

[75] Inventors: **Frank J. DiSanto**, North Hills; **Denis  
A. Krusos**, Lloyd Harbor; **Edward  
Lewit**, Roslyn Heights, all of N.Y.

[73] Assignee: **Copytele, Inc.**, Huntington Station,  
N.Y.

[21] Appl. No.: **313,987**

[22] Filed: **Sep. 28, 1994**

**Related U.S. Application Data**

[63] Continuation of Ser. No. 130,269, Oct. 1, 1993, abandoned.

[51] **Int. Cl.**<sup>6</sup> ..... **G09G 3/34**

[52] **U.S. Cl.** ..... **345/107; 345/48**

[58] **Field of Search** ..... 345/48, 49, 50,  
345/84, 85, 80, 87, 210, 105, 107; 241/20;  
359/296, 54

[56] **References Cited****U.S. PATENT DOCUMENTS**

3,892,563	7/1975	Ota	241/20
4,041,481	8/1977	Sato	345/107
4,203,106	5/1980	Dalisa	345/107
4,246,579	1/1981	Wiesner	345/210

4,655,897	4/1987	DiSanto et al.	259/296
4,732,830	3/1988	DiSanto et al.	359/54
4,742,345	5/1988	DiSanto et al.	345/107
4,947,157	8/1990	DiSanto et al.	345/107
5,053,763	10/1991	DiSanto et al.	345/107
5,066,946	11/1991	DiSanto et al.	345/107
5,174,882	12/1992	DiSanto et al.	204/299 R
5,223,115	6/1993	DiSanto et al.	204/299 R
5,266,937	11/1993	DiSanto et al.	345/107

*Primary Examiner*—Richard Hjerpe

*Assistant Examiner*—Steven J. Saras

*Attorney, Agent, or Firm*—Plevy & Associates

[57] **ABSTRACT**

An electrophoretic display includes a plurality of groups of intersecting row and column electrodes, and a plurality of parallel anode electrode segments disposed in spaced relation within a fluid-tight envelope containing a suspension of pigment particles in a dielectric fluid. Each respective group of row and column electrodes and a corresponding anode segment are indicative of a character line of displayed text. The display includes a line control system operable in a partial erase mode to partially erase a character line having a character thereof selected for erasure and operable in a rewriting mode to rewrite to the character line all characters not selected for erasure. The line control system is operable to alternate sequentially between the two modes until the selected character is simply erased or replaced entirely with a new character.

**19 Claims, 4 Drawing Sheets**